## **PRODUCT DATA SHEET:**

Product Description : R.C. INTERNAL SILVER LACQUER

Product Type : Epoxy

Recommended Uses : Internal silver coating for cans.

PRODUCT DATA:

Colour : Silver

% Solid By Weight : 38 +/- 2 %

Viscosity @30 Deg C # F4 : 80 - 90 SEC +/-5 SEC. By B4 at 30 Deg C.

Specific Gravity : 1.00 +/- 0.02

Self Life : 6 Months.

Acetone Resistance : Should pass more than 30 rubs.

APPLICATION:

Substrate : Tin & TFS

Application Method : Roller Coating

Thinner : HIM / 1100 Cleaning : HIM / 1100

Film Weight : 6 - 7 Mg./ Sq.Inch

Stoving Schedule : 170 - 180 Deg C for 12 Min.

Remark : High Slip hence recoatability or printing is not

possible.

MANUFACTURED AND QUALITY CONTROLLED UNDER LATEST QUALITY MANAGEMENT SYSTEM.

All details contain in this information sheet have been given to the best of our knowledge and belief. This technical information is intended only as a guide and no binding liability can be derived from it. All information, which refers to working with our products, must be adapted to take account of the local conditions and material used.

Regd. Off: D-501, Serenity, Behind Oshiwara Police Station, Andheri (W.), Mumbai - 400102. India.

 $Factory: Gut\ No.\ 37-B,\ Viilage\ Met,\ Taluka\ Wada,\ Dist.\ Palghar-421303.\ India. Tel.\ No.\ +91\ 9270081803\ /\ +919321615557\ Advisors +91932161557\ Advisors +91932161557\ Advisors +91932161557\ Advisors +91932161557\ Advisors +91932161557\ Advisors +9193216157\ Advisors +919321617\ Advisors +919321617\ Advisors +919321617\ Advisors +919321617\ Advi$ 

AN AN ISO 9001: 2008 CERTIFIED COMPANY