## **PRODUCT DATA SHEET:**

Product Description : R.C.GP.TONNED WHITE

Product Type : Alkyd

Recommended Uses : External white coating for general line containers

PRODUCT DATA:

Colour : Tonned White

% Solid By Weight : 57 +/- 2 %

Viscosity @30 Deg C # F4 : 120 - 140 SEC +/-5 SEC. By B4 at 30 Deg C.

Specific Gravity : 1.10 + -0.02Self Life : 12 Months.

APPLICATION:

Substrate : Tin & TFS

Application Method : Roller Coating

Thinner : HIM / 1100
Cleaning : HIM / 1100

Film Weight : 10 - 12 Mg./ Sq.Inch Stoving Schedule : 150 Deg C for 12 Min.

Remark : Tonning can be adjusted as per customer

requirement.

MANUFACTURED AND QUALITY CONTROLLED UNDER LATEST QUALITY MANAGEMENT SYSTEM.

All details contain in this information sheet have been given to the best of our knowledge and belief. This technical information is intended only as a guide and no binding liability can be derived from it. All information, which refers to working with our products, must be adapted to take account of the local conditions and material used.

Regd. Off: D-501, Serenity, Behind Oshiwara Police Station, Andheri (W.), Mumbai – 400102. India.

Factory : Gut No. 37-B, Viilage Met, Taluka Wada, Dist. Palghar – 421303. India.Tel. No. +91 9270081803 / +919321615557

www.harmonyinks.com E-Mail:-harmonyinks@yahoo.com / sales@harmonyinks.com

AN AN ISO 9001: 2008 CERTIFIED COMPANY